(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification⁷: H04L 27/38

(21) International Application Number:
PCT/SE2002/001325

(22) International Filing Date: 3 July 2002 (03.07.2002)

(25) Filing Language: English

(26) Publication Language: English

(71) Applicant (for all designated States except US): TELE-FONAKTIEBOLAGET LM ERICSSON (publ) [SE/SE]; S-126 25 Stockholm (SE).

(72) Inventors; and
(75) Inventors/Applicants (for US only): WEINHOLT, Dan, Rutger [SE/SE]; Enskärsgatan 15, S-421 60 Västra Frölunda (SE). GUSTAVSSON, Per-Olof, Gerhard [SE/SE]; Körsbärsvägen 21, S-435 43 Pixbo (SE).

(74) Agent: ERICSSON AB; Patent Unit West, SE-431 84 Mölndal (SE).

(81) Designated States (national): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB. GD. GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX. MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:
—   with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: EMBEDDED KEYING

(57) Abstract: Method of communicating digital data in which frames (8) are transmitted cyclically whereby a first number of symbols is transmitted according to a first keying mode (H) using a first constellation, and a second number of symbols is transmitted according to a second keying mode (L) using a second constellation. The first and second keying modes (H, L) are used at predetermined positions in the frame, whereby both the symbols according to the first and second keying mode carry information under at least an operative traffic phase.